


# Atlantic

Wall

IBS


INTERNATIONAL  
BUILDERS SUPPLY



Atlantic Lightgrey  
12"x36"




Dexa Lightgrey  
12"x36"




Atlantic Grey  
12"x36"



Dexa Grey  
12"x36"



Atlantic Darkgrey  
12"x36"



Dexa Darkgrey  
12"x36"

Matte  
Porcelain Tile  
Wall Tile  
White Body

# Atlantic

Wall



INTERNATIONAL BUILDERS SUPPLY

Technical Characteristics	ISO	Standard	Atlantic
Thickness Variation	10545-2		8.7mm ± 0.5mm
Straightness of Sides	10545-2		Short: 0.14% Long: ±0.06%
Orthogonality	10545-2		Short: 0.14% Long: ±0.06%
Warpage	10545-2		± 0.15%
Water Absorption	10545-3:97	> 10%	Passed
Breaking Strength	10545-4:15	≥ 600N	Passed
Modulus of Rupture	10545-4:15	≥ 12 N/mm <sup>2</sup>	Passed
Thermal Resistance	10545-9:13		Resistant
Crazing Resistance	10545-11:97	Demanded	Resistant

Acids and Bases	Weak Strong	10545-13	Min GLB Min GHB
Cleaning Products and Pool Reactive Agents		Min GB	Passed
Resistance to Stains		10545-14	Required Passed

Size	Thickness	Sqf/Box	Pieces/Box	Lbs/Box
12"x36"	11mm	11.625	4	41.446