


Concept

Floor and Wall

IBS

INTERNATIONAL
BUILDERS SUPPLY



Concept Mist
24"x 24" Rc
24"x 24" Rc Anti-slip
24"x 24"
24"x 24" Anti-slip
30"x 30" Rc
36"x 36" Rc



Concept Natural
24"x 24" Rc
24"x 24" Rc Anti-slip
24"x 24"
24"x 24" Anti-slip
30"x 30" Rc
36"x 36" Rc



Concept Classic
24"x 24" Rc
24"x 24" Rc Anti-slip
24"x 24"
24"x 24" Anti-slip
30"x 30" Rc
36"x 36" Rc



Concept Smoke
24"x 24" Rc
24"x 24" Rc Anti-slip
24"x 24"
24"x 24" Anti-slip
30"x 30" Rc
36"x 36" Rc

Matte
Porcelain Tile
Floor & Wall Tile
White Body

Concept

Floor and Wall



INTERNATIONAL
BUILDERS SUPPLY

Technical Characteristics	ISO	Standard	Concept
Average Deviation of Sides	10545-2		±0.1%
Thickness Variation	10545-2		± 5%
Straightness of Sides	10545-2		±0.22%
Orthogonality	10545-2		±0.22%
Central Curvature	10545-2		CC: -0.12% CV: +0.22%
Lateral Curvature	10545-2		CC: -0.12% CV: +0.22%
Warpage	10545-2		±0.22%
Water Absorption	10545-3:97	≤ 0.5%	Passed
Breaking Strength	10545-4:15	≥ 1300 N	Passed
Modulus of Rupture	10545-4:15	≥ 35 N/mm ²	Passed
Resistance to Surface Abrasion	10545-7:99	From 0 to 5	Class 3
Thermal Shock Resistance	10545-9:13		Passed
Crazing Resistance	10545-11:97		Passed
Slipperiness	UNE-ENV 12633:2003		C 1
Frost Resistance	10545-12:97	Required	Passed

Acids and Bases	Weak Strong		GLA GHA
Cleaning Products and Pool Reactive Agents		Min GB	Passed
Resistance to Stains	10545-14:98	Required	Passed
Surface Scratch Resistance	UNE 67101:85		5

Size	Thickness	Sqf/Box	Pieces/Box	Lbs/Box
24"x24" Rc	9mm	11.19	3	48.50
24"x24"	9mm	11.625	3	49.60
30"x30" Rc	10.2mm	12.055	2	56.217
36"x36" Rc	9mm	8.718	1	37.478