

Moon



INTERNATIONAL
BUILDERS SUPPLY



Moon Grey
24"x 24"
24"x 24" Rc
3"x 24"
3"x 24" Rc



Moon Bone
24"x 24"
24"x 24" Rc
3"x 24"
3"x 24" Rc



Moon Silver
24"x 24"
24"x 24" Rc
3"x 24"
3"x 24" Rc

Matte Finish
Floor & Wall Tile
White Body
Porcelain Tile

Moon



INTERNATIONAL
BUILDERS SUPPLY

| Technical Characteristics | ISO | Standard | Moon |
|--------------------------------|--------------------|------------------------|----------------------|
| Average Deviation of Sides | 10545-2 | | ± 0.1% |
| Thickness Variation | 10545-2 | | ± 5% |
| Straightness of Sides | 10545-2 | | ±0.22% |
| Orthogonality | 10545-2 | | ±0.22% |
| Central Curvature | 10545-2 | | CC: -0.12% CV:+0.22% |
| Lateral Curvature | 10545-2 | | CC: -0.12% CV:+0.22% |
| Warpage | 10545-2 | | ± 0.22% |
| Water Absorption | 10545-3:97 | ≤ 0.5% | Passed |
| Breaking Strength | 10545-4:15 | > 1300N | Passed |
| Modulus of Rupture | 10545-4:15 | ≥ 35 N/mm ² | Passed |
| Resistance to Surface Abrasion | 10545-7:99 | From 0 to 5 | Class 4 |
| Thermal Shock Resistance | 10545-9:13 | | Passed |
| Crazing Resistance | 10545-11:97 | Demanded | Passed |
| Slipperiness | UNE-ENV 12633:2003 | | C1 |
| Frost Resistance | 10545-12:97 | Required | Passed |

| | | | |
|---|----------------|-------------|------------|
| Acids and Bases | Weak Strong | | GLA GHA |
| Cleaning Products and Pool Reactive Agents | | Min GB | Passed |
| Resistance to Stains | 10545-14:98 | Required | Passed |
| Surface Scratch Resistance | UNE 67101:85 | From 4 to 7 | 5 |

| Size | Thickness | Sqf/Box | Pieces/Box | Lbs/Box |
|------------|-----------|---------|------------|---------|
| 24"x24" | 10mm | 11.625 | 3 | 52.91 |
| 24"x24" Rc | 10mm | 11.194 | 3 | 51.808 |
| 3"x24" | 10mm | | 15 | 33.069 |
| 24"x24" Rc | 10mm | | 15 | 33.069 |