

# Project

Floor and Wall

IBS

INTERNATIONAL  
BUILDERS SUPPLY



Project Desert  
30"x 30"  
3"x 30"



Project Grey  
30"x 30"  
3"x 30"



Project Taupe  
30"x 30"  
3"x 30"

Matte  
Porcelain Tile  
Floor & Wall Tile

# Project

## Floor and Wall



INTERNATIONAL  
BUILDERS SUPPLY

| Technical Characteristics                  | ISO                | Standard               | Project               |
|--|--------------------|------------------------|-----------------------|
| Average Deviation of Sides                 | 10545-2            |                        | ± 0.08%               |
| Thickness Variation                        | 10545-2            |                        | ± 0.5mm               |
| Straightness of Sides                      | 10545-2            |                        | ±0.07%                |
| Orthogonality                              | 10545-2            |                        | ±0.10%                |
| Central Curvature                          | 10545-2            |                        | CC: -0.12% CV: +0.20% |
| Lateral Curvature                          | 10545-2            |                        | CC: -0.10% CV: +0.18% |
| Warpage                                    | 10545-2            |                        | CC: -0.10% CV: +0.18% |
| Water Absorption                           | 10545-3:97         | ≤ 0.5%                 | Passed                |
| Breaking Strength                          | 10545-4:15         | ≥ 1300 N               | Passed                |
| Modulus of Rupture                         | 10545-4:15         | ≥ 35 N/mm <sup>2</sup> | Passed                |
| Resistance to Surface Abrasion             | 10545-7:99         | From 0 to 5            | Class 4               |
| Thermal Shock Resistance                   | 10545-9:13         |                        | Passed                |
| Crazing Resistance                         | 10545-11:97        |                        | Passed                |
| Slipperiness                               | UNE-ENV 12633:2003 |                        | C 1                   |
| Frost Resistance                           | 10545-12:97        | Required               | Passed                |
| Acids and Bases                            | Weak<br>Strong     |                        | GLA<br>GHA            |
| Cleaning Products and Pool Reactive Agents |                    | Min GB                 | Passed                |
| Resistance to Stains                       | 10545-14:98        | Required               | Passed                |
| Surface Scratch Resistance                 | UNE 67101:85       |                        | 9                     |

| Size    | Thickness | Sqf/Box | Pieces/Box | Lbs/Box |
|---------|-----------|---------|------------|---------|
| 30"x30" | 10.2mm    | 12.109  | 2          | 56.217  |
| 3"x30"  | 10.2mm    |         | 15         | 44.09   |