

# River

Floor and Wall

IBS

INTERNATIONAL  
BUILDERS SUPPLY



River Sand  
30"x 30" Rc  
24"x 24"  
24"x 24" Rc  
3"x 30"  
3"x 24"



River Grey  
30"x 30" Rc  
24"x 24"  
24"x 24" Rc  
3"x 30"  
3"x 24"



River Coal  
30"x 30" Rc  
3"x 30"

Matte  
Porcelain Tile  
Floor & Wall Tile

# River

## Floor and Wall



INTERNATIONAL  
BUILDERS SUPPLY

Technical Characteristics	ISO	Standard	River
Average Deviation of Sides	10545-2		±0.1%
Thickness Variation	10545-2		10mm ± 5%
Straightness of Sides	10545-2		±0.22%
Orthogonality	10545-2		±0.22%
Central Curvature	10545-2		CC: -0.12% CV: +0.22%
Lateral Curvature	10545-2		CC: -0.12% CV: +0.22%
Warpage	10545-2		±0.22%
Water Absorption	10545-3:97	≤ 0.5%	Passed
Breaking Strength	10545-4:15	≥ 1300 N	Passed
Modulus of Rupture	10545-4:15	≥ 35 N/mm <sup>2</sup>	Passed
Resistance to Surface Abrasion	10545-7:99	From 0 to 5	Class 4
Thermal Shock Resistance	10545-9:13		Passed
Crazing Resistance	10545-11:97	Required	Passed
Slipperiness	UNE-ENV 12633:2003		C 1
Frost Resistance	10545-12:97	Required	Passed

Acids and Bases	Weak Strong		GLA GHA
Cleaning Products and Pool Reactive Agents		Min GB	Passed
Resistance to Stains	10545-14:98	Required	Passed
Surface Scratch Resistance	UNE 67101:85	From 4 to 7	5

Size	Thickness	Sqf/Box	Pieces/Box	Lbs/Box
30"x30" Rc	10.2mm	12.109	2	56.217
24"x24"	10mm	11.625	3	52.91
24"x24" Rc	10mm	11.19	3	51.808
3"x30"	10.2mm		15	44.09
3"x24"	10mm		15	33.069