


Spirit

Wall

IBS

INTERNATIONAL
BUILDERS SUPPLY



Spirit Silver
12"x36"



Spirit Grey
12"x36"



Spirit Module Silver
12"x36"



Spirit Module Grey
12"x36"



Spirit Silver Dec
12"x36"



Spirit Grey Dec
12"x36"

Satin Finish
Wall Tile
White Body
Porcelain Tile

Spirit

Wall



INTERNATIONAL
BUILDERS SUPPLY

Technical Characteristics	ISO	Standard	Spirit
Thickness Variation	10545-2		10.2 ± 10%
Straightness of Sides	10545-2		± 0.07%
Orthogonality	10545-2		± 0.07%
Curvature	10545-2		Short: CC: -0.06% CV: +0.12% Long: CC: -0.06% CV: +0.12%
Water Absorption	10545-3:97	> 10%	Passed
Breaking Strength	10545-4:15	≥ 600N	Passed
Modulus of Rupture	10545-4:15	≥ 12 N/mm ²	Passed
Lineal Thermal Expansion	10545-8:14	9x10 ⁻⁶ K ⁻¹ max	6.5x10 ⁻⁶ K ⁻¹
Thermal Resistance	10545-9:13		Passed
Crazing Resistance	10545-11:97	Demanded	Resistant

Acids and Bases	Weak Strong	10545-13	GLA GHA
Cleaning Products and Pool Reactive Agents		Min GB	GA
Resistance to Stains		Required	Class 5

Size	Thickness	Sqf/Box	Pieces/Box	Lbs/Box
12"x36"	10.6mm	11.625	4	41.535