





Hamptons

Color	Hamptons
Size	7" x 48"
Overall Thickness	2mm
Wearlayer Thickness	6mil
Textures	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
2mm 6mil Thickness Wearlayer	Size / Squareness	ASTM F2055	(Pass) / (Pass)
	Thickness	ASTM F386	(Pass)
Commercial Multi-Family SemiGloss	Flexibility	ASTM F137	(Pass)
	Dimensional Stability	ASTM F2199	(Pass)
Straight Edge Deep Wood Embossed Shade Variation	Resistance to Chemicals	ASTM F925	(Pass)
	Resistance to light	ASTM F1515	(Pass)
	Resistance to heat	ASTM F1514	(Pass)
	Formaldehyde	ASTM D 6007	Not detected
	Smoke Density	ASTM E662	(Pass)
Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Ontions	Details

Sizes:

7" x 48" | 6" x 36" | 6" x 48"

Thickness:

2mm/6mil | 2mm/8mil | 2mm/12mil 2.5mm/20mil | 3mm/20mil 3mm/28mil

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish

