TUFFPLANK

OSCScertifi

Aberdeen

LVT Plank

SUPPLY

Nantucket

Color	Nantucket
Size	7 x 48 in
Overall Thickness	2 mm
Wearlayer Thickness	6 mil
Textures	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Test	Results
Flammability Static Load Limit Abrasion Resistance Formaldehyde Antibacterial Activity Castor Chair Resistance Stain Resistance Smoke Density Size / Squareness Thickness Flexibility Dimensional Stability Chemical Resistance Heat / Light Resistance Workmanship, Finish Appearance	BF1-S1 (Pass) Group T Class 1, Not detected Rating 1 No effect (Pass) (Pass) <450 (Pass) / (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) (Pass)
Details	
All material 100% recyclable after use Test based on Deep Embossed Finish	
	Flammability Static Load Limit Abrasion Resistance Formaldehyde Antibacterial Activity Castor Chair Resistance Stain Resistance Smoke Density Size / Squareness Thickness Flexibility Dimensional Stability Chemical Resistance Heat / Light Resistance Workmanship, Finish Appearance Details All material 100% recyclable at

