



## Rockport

<b>Color</b>	Rockport
<b>Size</b>	7" x 48"
<b>Overall Thickness</b>	2mm
<b>Wearlayer Thickness</b>	6mil
<b>Textures</b>	Deep Wood Embossed
<b>Edge</b>	Straight
<b>Finish</b>	Semi Gloss
<b>Install</b>	Glue Down

Symbols	Test	Method	Results
<b>Glue Down</b>	Size / Squareness	ASTM F2055	(Pass) / (Pass)
<b>2mm Thickness</b>	Thickness	ASTM F386	(Pass)
<b>6mil Wearlayer</b>	Flexibility	ASTM F137	(Pass)
<b>Commercial</b>	Dimensional Stability	ASTM F2199	(Pass)
<b>Multi-Family</b>	Resistance to Chemicals	ASTM F925	(Pass)
<b>Semi Gloss</b>	Resistance to light	ASTM F1515	(Pass)
<b>Straight Edge</b>	Resistance to heat	ASTM F1514	(Pass)
<b>Deep Wood Embossed</b>	Formaldehyde	ASTM D 6007	Not detected
<b>V3 Shade Variation</b>	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial &amp; commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options	Details
<p><b>Sizes:</b> 7" x 48"   6" x 36"   6" x 48"</p> <p><b>Thickness:</b> 2mm/6mil   2mm/8mil   2mm/12mil 2.5mm/20mil   3mm/20mil 3mm/28mil</p>	<p>All material 100% recyclable after use.</p> <p>Test based on Deep Wood Embossed Finish</p>

