



## Vineyard

<b>Color</b>	Vineyard
<b>Size</b>	7" x 48"
<b>Overall Thickness</b>	2mm
<b>Wearlayer Thickness</b>	6mil
<b>Textures</b>	Deep Wood Embossed
<b>Edge</b>	Straight
<b>Finish</b>	Semi Gloss
<b>Install</b>	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wearlayer	Flexibility	ASTM F137	(Pass)
 Commercial	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options	Details
<b>Sizes:</b> 7" x 48"   6" x 36"   6" x 48"	All material 100% recyclable after use.  Test based on Deep Wood Embossed Finish
<b>Thickness:</b> 2mm/6mil   2mm/8mil   2mm/12mil 2.5mm/20mil   3mm/20mil 3mm/28mil	

