

TUFFPLANK













Natural Foundations

LVT Plank



Tobacco

Color	Tobacco
Size	6" x 36"
Overall Thickness	2mm
Wearlayer Thickness	6mil
Textures	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wearlayer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 SemiGloss	Resistance to light	ASTM F1515	(Pass)
 Dry Back	Resistance to heat	ASTM F1514	(Pass)
 Straight Edge	Formaldehyde	ASTM D 6007	Not detected
 Deep Wood Embossed	Smoke Density	ASTM E662	(Pass)
 V2 Shade Variation	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

Size Options

6" x 36"

Details

Available only with virgin vinyl.
All material 100% recyclable after use.
Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services