

**TUFFPLANK**

# Purist / 2mm

LVT Plank



Limited Stock In The USA

## Cashmere

**Color** Cashmere

**Size** 6" x 36"

**Overall Thickness** 2mm

**Wearlayer Thickness** 6mil

**Textures** Satin Wood

**Edge** Straight

**Finish** Semi Gloss

**Install** Glue Down

Symbols	Test	Method	Results
	Size / Squareness	ASTM F2055	(Pass) / (Pass)
	Thickness	ASTM F386	(Pass)
	Flexibility	ASTM F137	(Pass)
	Dimensional Stability	ASTM F2199	(Pass)
	Resistance to Chemicals	ASTM F925	(Pass)
	Resistance to light	ASTM F1515	(Pass)
	Resistance to heat	ASTM F1514	(Pass)
	Formaldehyde	ASTM D 6007	Not detected
	Smoke Density	ASTM E662	(Pass)
	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

**Size Options**

7" x 48"

**Details**

Available only with virgin vinyl.  
All material 100% recyclable after use.  
Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services