

TUFFPLANK

Purist / 2mm

LVT Plank



Limited Stock In The USA

Shadow White

Color Shadow White

Size 6" x 36"

Overall Thickness 2mm

Wearlayer Thickness 6mil

Textures Satin Wood

Edge Straight

Finish Semi Gloss

Install Glue Down

| Symbols | Test | Method | Results |
|---------|-------------------------|-------------|-----------------|
| | Size / Squareness | ASTM F2055 | (Pass) / (Pass) |
| | Thickness | ASTM F386 | (Pass) |
| | Flexibility | ASTM F137 | (Pass) |
| | Dimensional Stability | ASTM F2199 | (Pass) |
| | Resistance to Chemicals | ASTM F925 | (Pass) |
| | Resistance to light | ASTM F1515 | (Pass) |
| | Resistance to heat | ASTM F1514 | (Pass) |
| | Formaldehyde | ASTM D 6007 | Not detected |
| | Smoke Density | ASTM E662 | (Pass) |
| | Critical Radiant Flux | ASTM E648 | (Pass) |
| | Workmanship, Finish | | (Pass) |
| | Appearance | | (Pass) |

Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

Size Options

7" x 48"

Details

Available only with virgin vinyl.
All material 100% recyclable after use.
Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services