# TUFF**PLANK**

# Purist / 2mm
## LVT Plank

**IB SUPPLY**

Limited Stock In The USA

# Venice Boardwalk

| | |
|---:|:---|
| **Color** | Venice Boardwalk |
| **Size** | 6" x 36" |
| **Overall Thickness** | 2mm |
| **Wearlayer Thickness** | 6mil |
| **Textures** | Satin Wood |
| **Edge** | Straight |
| **Finish** | Semi Gloss |
| **Install** | Glue Down |

## Symbols

Glue Down
**2mm** Thickness
**6mil** Wearlayer

**R** Residential
Multi-Family
SemiGloss

Dry Back
Straight Edge
Satin Wood

**V4** Shade Variation

Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

| Test | Method | Results |
|---|---|---|
| Size / Squareness | ASTM F2055 | (Pass) / (Pass) |
| Thickness | ASTM F386 | (Pass) |
| Flexibility | ASTM F137 | (Pass) |
| Dimensional Stability | ASTM F2199 | (Pass) |
| Resistance to Chemicals | ASTM F925 | (Pass) |
| Resistance to light | ASTM F1515 | (Pass) |
| Resistance to heat | ASTM F1514 | (Pass) |
| Formaldehyde | ASTM D 6007 | Not detected |
| Smoke Density | ASTM E662 | (Pass) |
| Critical Radiant Flux | ASTM E648 | (Pass) |
| Workmanship, Finish | | (Pass) |
| Appearance | | (Pass) |

| Size Options | Details |
|---|---|
| 7" x 48" | Available only with virgin vinyl. All material 100% recyclable after use. Test based on Deep Wood Embossed Finish |

floor score
CERTIFIED BY SCS Global Services