

Spectrum LVT Plank





TPSP-101

| Color | TPSP - 101 |
|---------------------|--------------------|
| Size | 6" x 36" |
| Overall Thickness | 2mm |
| Wearlayer Thickness | 6mil |
| Textures | Deep Wood Embossed |
| Edge | Straight |
| Finish | Semi Gloss |
| Install | Glue Down |

| Symbols | Test | Method | Results |
|---|-------------------------|-------------|-----------------|
| 2mm 6mil Thickness Glue Down | Size / Squareness | ASTM F2055 | (Pass) / (Pass) |
| | Thickness | ASTM F386 | (Pass) |
| | Flexibility | ASTM F137 | (Pass) |
| Residential Multi-Family SemiGloss | Dimensional Stability | ASTM F2199 | (Pass) |
| Straight Edge Deep Wood Embossed Shade Variation | Resistance to Chemicals | ASTM F925 | (Pass) |
| | Resistance to light | ASTM F1515 | (Pass) |
| | Resistance to heat | ASTM F1514 | (Pass) |
| | Formaldehyde | ASTM D 6007 | Not detected |
| | Smoke Density | ASTM E662 | (Pass) |
| Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a | Critical Radiant Flux | ASTM E648 | (Pass) |
| | Workmanship, Finish | | (Pass) |
| minimum of 20mil for light commercial & commercial applications. | Appearance | | (Pass) |

Size Options Details

7" x 48"

All material 100% recyclable after use. Test based on Deep Wood Embossed Finish

