

## TPSP - 103

**Color** TPSP - 103

**Size** 6" x 36"

**Overall Thickness** 2mm

**Wearlayer Thickness** 6mil

**Textures** Deep Wood Embossed

**Edge** Straight

**Finish** Semi Gloss

**Install** Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wearlayer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial &amp; commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

### Size Options

7" x 48"

### Details

All material 100% recyclable after use.  
Test based on Deep Wood Embossed Finish