

# TUFFPLANK

# Spectrum

LVT Plank



Stocked in limited quantities for mock ups, relay, or to get initiative started.

## TPSP - 108

**Color** TPSP - 108

**Size** 6" x 36"

**Overall Thickness** 2mm









**Wearlayer Thickness** 6mil

**Textures** Deep Wood Embossed

**Edge** Straight

**Finish** Semi Gloss

**Install** Glue Down

| Symbols  | Test                    | Method      | Results         |
|--|-------------------------|-------------|-----------------|
| <br>Glue Down   | Size / Squareness       | ASTM F2055  | (Pass) / (Pass) |
| <br>2mm Thickness   | Thickness               | ASTM F386   | (Pass)          |
| <br>6mil Wearlayer  | Flexibility             | ASTM F137   | (Pass)          |
| <br>Residential   | Dimensional Stability   | ASTM F2199  | (Pass)          |
| <br>Multi-Family  | Resistance to Chemicals | ASTM F925   | (Pass)          |
| <br>Semi Gloss  | Resistance to light     | ASTM F1515  | (Pass)          |
| <br>Straight Edge   | Resistance to heat      | ASTM F1514  | (Pass)          |
| <br>Deep Wood Embossed  | Formaldehyde            | ASTM D 6007 | Not detected    |
| <br>Shade Variation   | Smoke Density           | ASTM E662   | (Pass)          |
| Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications. | Critical Radiant Flux   | ASTM E648   | (Pass)          |
|  | Workmanship, Finish     |             | (Pass)          |
|  | Appearance              |             | (Pass)          |

### Size Options

7" x 48"

### Details

All material 100% recyclable after use.  
Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services