



Packing



Details

Technical Specifications & Features

			5			
Thermally modified wood mosaic tile	Thermal Modification	Process of treating the wood with a controlled pyrolysis for 2 -3 days.	15.31" x 9.57"	10 pc	10.2 SF	9 Lbs
Sheet Size: 15.31" x 9.57"		Through the Thermal Process, the wood's	Format			
Thickness: 9/16"		molecular structure is modified; all the organic				
Grout free with 1mm gap between chips		compounds and water retained in the wood is removed.	-		F, F	-
UV Clear Coat	Fire Resistance	Class C3				
Mesh Mounted		May be installed on a wall near electric fireplace with a temperature not to exceed 210°F.			-	
Benefits		Not recommended for installation on a wall near wood burning fireplace or stove.			4	-
• D. wikle	Durability	Class 1-3 EN 350-2		-		
DurableResistant to micro-organisms and insects	Recommended Adhesives	Mapei Ultrabond ECO GPT Mapei ECO 985 Boston Best Adhesive - Bond Hardwood	Natural Wood			
• Up to 90% reduced shrinking and swelling		Liquid Nails Heavy Duty - Construction Adhesive Loctite PL Premium Polyurethane				
 Environmentally friendly No chemical staining 		Weldwood Contact Cement - Construction Adhesive For a more uniform result, use a brown color		Commercial	Natural	
• 100% sourced in North America using sustainable	Character	adhesive.				
harvesting	Cleaning	Warm soapy water. Avoid chemical and abrasive products.				
 Handmade in the USA 		p. 6 6 6 6 6 7				