

Details	Technical Specifications & Features		Packing	Pcs/Box	SF/Box	Lbs/Box
Thermally modified wood mosaic tile	Thermal Modification	Process of treating the wood with a controlled pyrolysis for 2 -3 days.	12.56" x 11.81"	10рс	10.3 SF	11 Lbs
Sheet Size: 12.56" x 11.81"		Through the Thermal Process, the wood's	Format			
Thickness: 9/16"	Fire Resistance  Durability  Recommended Adhesives  Cleaning	molecular structure is modified; all the organic compounds and water retained in the wood is removed.				
Grout free with 1mm gap between chips						
UV Clear Coat		Class C3				
Mesh Mounted		May be installed on a wall near electric fireplace with a temperature not to exceed 210°F.				
Benefits		Not recommended for installation on a wall near wood burning fireplace or stove.				
• Durable		Class 1-3 EN 350-2				
Resistant to micro-organisms and insects		Mapei Ultrabond ECO GPT Mapei ECO 985 Boston Best Adhesive - Bond Hardwood Liquid Nails Heavy Duty - Construction Adhesive Loctite PL Premium Polyurethane	Natural Wood  Symbols  Residential Commercial Natural			
<ul> <li>Up to 90% reduced shrinking and swelling</li> </ul>						
<ul> <li>Environmentally friendly No chemical staining</li> </ul>		Weldwood Contact Cement - Construction Adhesive  For a more uniform result, use a brown color adhesive.  Warm soapy water. Avoid chemical and abrasive products.				
<ul> <li>100% sourced in North America using sustainable harvesting</li> </ul>						
<ul> <li>Handmade in the USA</li> </ul>		products.				

• Handmade in the USA