

| Details | Technical Specifications & Features | |
|--|-------------------------------------|--|
| Thermally modified wood mosaic tile | Thermal Modification | Process of treating the wood with a controlled pyrolysis for 2 -3 days. |
| Sheet Size: 5.12" x 5.12" | | Through the Thermal Process, the wood's |
| Thickness: 9/16" | | molecular structure is modified; all the organic |
| Grout free with 1mm gap between chips | | compounds and water retained in the wood is removed. |
| UV Clear Coat | Fire Resistance | Class C3 |
| Mesh Mounted | | May be installed on a wall near electric fireplace with a temperature not to exceed 210°F. |
| Benefits | | Not recommended for installation on a wall near wood burning fireplace or stove. |
| 5 11 | Durability | Class 1-3 EN 350-2 |
| Durable Resistant to micro-organisms | Recommended Adhesives | Mapei Ultrabond ECO GPT Mapei ECO 985 |

Cleaning

and insects

and swelling

harvesting

• Up to 90% reduced shrinking

• Environmentally friendly No chemical staining

• 100% sourced in North

• Handmade in the USA

America using sustainable

Mapei ECO 985

adhesive.

products.

5.12" x 5.12" 60 pc 10.8 SF 15 Lbs

SF/Box

Lbs/Box

Pcs/Box

Format

Packing



Natural Wood

Symbols



Warm soapy water. Avoid chemical and abrasive

Boston Best Adhesive - Bond Hardwood

For a more uniform result, use a brown color

Loctite PL Premium Polyurethane

Liquid Nails Heavy Duty - Construction Adhesive

Weldwood Contact Cement - Construction Adhesive