

TUFFPLANK

Riverton

LVT Plank



Stocked in limited quantities for mock ups, relay, or to get initiative started.

Columbia

Color Columbia

Size 7" x 48"

Overall Thickness 2mm










Wearlayer Thickness 6mil

Textures Deep Wood Embossed

Edge Straight

Finish Semi Gloss

Install Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wearlayer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services