

## Potomac

**Color** Potomac

**Size** 7" x 48"

**Overall Thickness** 2mm

**Wear Layer Thickness** 6mil

**Texture** Deep Wood Embossed

**Edge** Straight

**Finish** Semi Gloss

**Install** Glue Down

Symbols	Test	Method	Results
<b>Glue Down</b>	Size / Squareness	ASTM F2055	(Pass) / (Pass)
<b>2mm Thickness</b>	Thickness	ASTM F386	(Pass)
<b>6mil Wear Layer</b>	Flexibility	ASTM F137	(Pass)
<b>Residential</b>	Dimensional Stability	ASTM F2199	(Pass)
<b>Multi-Family</b>	Resistance to Chemicals	ASTM F925	(Pass)
<b>Semi Gloss</b>	Resistance to light	ASTM F1515	(Pass)
<b>Straight Edge</b>	Resistance to heat	ASTM F1514	(Pass)
<b>Deep Wood Embossed</b>	Formaldehyde	ASTM D 6007	Not detected
<b>Shade Variation</b>	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial &amp; commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

### Options

**Sizes:**  
7" x 48" | 6" x 36" | 6" x 48"

**Thickness:**  
2mm/6mil | 2mm/8mil | 2mm/12mil  
2.5mm/20mil | 3mm/20mil  
3mm/28mil

### Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services