

# TUFFPLANK™

## Riverton

LVT Plank



Stocked in limited quantities for mock ups, relay, or to get initiative started.

## Trinity

**Color** Trinity

**Size** 7" x 48"

**Overall Thickness** 2mm

**Wear Layer Thickness** 6mil

**Textures** Deep Wood Embossed

**Edge** Straight

**Finish** Semi Gloss

**Install** Glue Down

### Symbols



Glue Down



2mm Thickness



6mil Wearlayer



Residential



Multi-Family



Semi Gloss



Straight Edge



Deep Wood Embossed



V3 Shade Variation

Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

### Test

Size / Squareness

Thickness

Flexibility

Dimensional Stability

Resistance to Chemicals

Resistance to light

Resistance to heat

Formaldehyde

Smoke Density

Critical Radiant Flux

Workmanship, Finish

Appearance

### Method

ASTM F2055

ASTM F386

ASTM F137

ASTM F2199

ASTM F925

ASTM F1515

ASTM F1514

ASTM D 6007

ASTM E662

ASTM E648

### Results

(Pass) / (Pass)

(Pass)

(Pass)

(Pass)

(Pass)

(Pass)

(Pass)

Not detected

(Pass)

(Pass)

(Pass)

(Pass)

### Options

#### Sizes:

7" x 48" | 6" x 36" | 6" x 48"

#### Thickness:

2mm/6mil | 2mm/8mil | 2mm/12mil

2.5mm/20mil | 3mm/20mil

3mm/28mil

### Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish

