

TUFFPLANK

Riverton

LVT Plank



Brazos

Color Brazos

Size 7" x 48"

Overall Thickness 2mm










Wear Layer Thickness 6mil

Texture Deep Wood Embossed

Edge Straight

Finish Semi Gloss

Install Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services



Columbia

Color	Columbia
Size	7" x 48"
Overall Thickness	2mm
Wear Layer Thickness	6mil
Texture	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
2mm Thickness	Thickness	ASTM F386	(Pass)
6mil Wear Layer	Flexibility	ASTM F137	(Pass)
Residential	Dimensional Stability	ASTM F2199	(Pass)
Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
Semi Gloss	Resistance to light	ASTM F1515	(Pass)
Straight Edge	Resistance to heat	ASTM F1514	(Pass)
Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
V3 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services



Hudson

Color	Hudson
Size	7" x 48"
Overall Thickness	2mm
Wear Layer Thickness	6mil
Texture	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options	Details
<p>Sizes: 7" x 48" 6" x 36" 6" x 48"</p> <p>Thickness: 2mm/6mil 2mm/8mil 2mm/12mil 2.5mm/20mil 3mm/20mil 3mm/28mil</p>	<p>All material 100% recyclable after use.</p> <p>Test based on Deep Wood Embossed Finish</p>



Potomac

Color Potomac

Size 7" x 48"

Overall Thickness 2mm

Wear Layer Thickness 6mil

Texture Deep Wood Embossed

Edge Straight

Finish Semi Gloss

Install Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services



St. Lawrence

Color	St. Lawrence
Size	7" x 48"
Overall Thickness	2mm
Wear Layer Thickness	6mil
Texture	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options	Details
<p>Sizes: 7" x 48" 6" x 36" 6" x 48"</p> <p>Thickness: 2mm/6mil 2mm/8mil 2mm/12mil 2.5mm/20mil 3mm/20mil 3mm/28mil</p>	<p>All material 100% recyclable after use.</p> <p>Test based on Deep Wood Embossed Finish</p>





Trinity

Color	Trinity
Size	7" x 48"
Overall Thickness	2mm
Wear Layer Thickness	6mil
Texture	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish












CERTIFIED BY SCS Global Services



Wabash

Color	Wabash
Size	7" x 48"
Overall Thickness	2mm
Wear Layer Thickness	6mil
Texture	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



TUFFPLANK










Riverton

LVT Plank



Yukon

Color	Yukon
Size	7" x 48"
Overall Thickness	2mm
Wear Layer Thickness	6mil
Texture	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols	Test	Method	Results
 Glue Down	Size / Squareness	ASTM F2055	(Pass) / (Pass)
 2mm Thickness	Thickness	ASTM F386	(Pass)
 6mil Wear Layer	Flexibility	ASTM F137	(Pass)
 Residential	Dimensional Stability	ASTM F2199	(Pass)
 Multi-Family	Resistance to Chemicals	ASTM F925	(Pass)
 Semi Gloss	Resistance to light	ASTM F1515	(Pass)
 Straight Edge	Resistance to heat	ASTM F1514	(Pass)
 Deep Wood Embossed	Formaldehyde	ASTM D 6007	Not detected
 Shade Variation	Smoke Density	ASTM E662	(Pass)
<p>Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.</p>	Critical Radiant Flux	ASTM E648	(Pass)
	Workmanship, Finish		(Pass)
	Appearance		(Pass)

Options

Sizes:
7" x 48" | 6" x 36" | 6" x 48"

Thickness:
2mm/6mil | 2mm/8mil | 2mm/12mil
2.5mm/20mil | 3mm/20mil
3mm/28mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services