



Potomac

Color	Potomac
Size	7" x 48"
Overall Thickness	2mm
Wearlayer Thickness	6 mil
Textures	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Symbols



Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

Test

Flammability
 Static Load Limit
 Abrasion Resistance
 Formaldehyde
 Antibacterial Activity
 Castor Chair Resistance
 Stain Resistance
 Smoke Density
 Size / Squareness
 Thickness
 Flexibility
 Dimensional Stability
 Chemical Resistance
 Heat / Light Resistance
 Workmanship, Finish
 Appearance

Results

BF1-S1
 (Pass)
 Group T
 Class 1, Not detected
 Rating 1
 No effect (Pass)
 (Pass)
 <450
 (Pass) / (Pass)
 (Pass)
 (Pass)
 (Pass)
 (Pass)
 (Pass) / (Pass)
 (Pass)
 (Pass)

Options

Sizes:
 7" x 48" | 6" x 36" | 6" x 48"

Thickness:
 2mm / 6 mil | 2mm / 8 mil | 2mm / 12 mil
 2.5mm / 20 mil | 3mm / 20 mil
 3mm / 28 mil

Details

All material 100% recyclable after use
 Test based on Deep Wood Embossed Finish



Scan for complete warranty information

