

# TUFFPLANK

# Riverton

LVT Plank



Limited Stock In The USA



## Trinity

<b>Color</b>	Trinity
<b>Size</b>	7" x 48"
<b>Overall Thickness</b>	2mm
<b>Wearlayer Thickness</b>	6 mil
<b>Textures</b>	Deep Wood Embossed
<b>Edge</b>	Straight
<b>Finish</b>	Semi Gloss
<b>Install</b>	Glue Down

### Symbols



Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications.

### Test

Flammability  
 Static Load Limit  
 Abrasion Resistance  
 Formaldehyde  
 Antibacterial Activity  
 Castor Chair Resistance  
 Stain Resistance  
 Smoke Density  
 Size / Squareness  
 Thickness  
 Flexibility  
 Dimensional Stability  
 Chemical Resistance  
 Heat / Light Resistance  
 Workmanship, Finish  
 Appearance

### Results

BF1-S1  
 (Pass)  
 Group T  
 Class 1, Not detected  
 Rating 1  
 No effect (Pass)  
 (Pass)  
 <450  
 (Pass) / (Pass)  
 (Pass)  
 (Pass)  
 (Pass)  
 (Pass)  
 (Pass) / (Pass)  
 (Pass)  
 (Pass)

### Options

Sizes:  
7" x 48" | 6" x 36" | 6" x 48"

Thickness:  
2mm / 6 mil | 2mm / 8 mil | 2mm / 12 mil  
2.5mm / 20 mil | 3mm / 20 mil  
3mm / 28 mil

### Details

All material 100% recyclable after use  
Test based on Deep Wood Embossed Finish



Scan for complete warranty information



CERTIFIED BY SCS Global Services