

LVT Plank





Yukon

Color	Yukon
Size	7" x 48"
Overall Thickness	2mm
Wearlayer Thickness	6 mil
Textures	Deep Wood Embossed
Edge	Straight
Finish	Semi Gloss
Install	Glue Down

Test

Symbols



applications.







Multifamiy units are considered residential and public spaces

are considered light commercial. Wearlayer thickness must

be a minimum of 20mil for light commercial & commercial





Flammability Static Load Limit Abrasion Resistance Formaldehyde Antibacterial Activity Castor Chair Resistance Stain Resistance Smoke Density Size / Squareness Thickness Flexibility **Dimensional Stability** Chemical Resistance

Heat / Light Resistance

Workmanship, Finish

Group T Class 1, Not detected Rating 1 No effect (Pass) (Pass) <450 (Pass) / (Pass) (Pass) (Pass) (Pass) (Pass) (Pass) / (Pass) (Pass) (Pass)

Results

BF1-S1

(Pass)

Options

Sizes:

7" x 48" | 6" x 36" | 6" x 48"

Thickness: 2mm / 6 mil | 2mm / 8 mil | 2mm / 12 mil 2.5mm / 20 mil | 3mm / 20 mil 3mm / 28 mil

Details

Appearance

All material 100% recyclable after use Test based on Deep Wood Embossed Finish



Scan for complete warranty information

