

TUFFPLANK

Aberdeen

FAST TRACK ESSENTIALS PROGRAM

LVT Plank



Stocked in limited quantities for mock ups, relay, or to get initiative started.

Long Branch

Color Long Branch

Size 7" x 48"

Overall Thickness 2mm










Wearlayer Thickness 6mil

Textures Deep Wood Embossed

Edge Straight

Finish Semi Gloss

Install Glue Down

| Symbols | Test | Method | Results |
|--|-------------------------|-------------|-----------------|
|  Glue Down | Size / Squareness | ASTM F2055 | (Pass) / (Pass) |
|  2mm Thickness | Thickness | ASTM F386 | (Pass) |
|  6mil Wearlayer | Flexibility | ASTM F137 | (Pass) |
|  Commercial | Dimensional Stability | ASTM F2199 | (Pass) |
|  Multi-Family | Resistance to Chemicals | ASTM F925 | (Pass) |
|  Semi Gloss | Resistance to light | ASTM F1515 | (Pass) |
|  Straight Edge | Resistance to heat | ASTM F1514 | (Pass) |
|  Deep Wood Embossed | Formaldehyde | ASTM D 6007 | Not detected |
|  V3 Shade Variation | Smoke Density | ASTM E662 | (Pass) |
| Multifamily units are considered residential and public spaces are considered light commercial. Wearlayer thickness must be a minimum of 20mil for light commercial & commercial applications. | Critical Radiant Flux | ASTM E648 | (Pass) |
| | Workmanship, Finish | | (Pass) |
| | Appearance | | (Pass) |

Size:

7" x 48"

Thickness:

2mm/6mil

Details

All material 100% recyclable after use.

Test based on Deep Wood Embossed Finish



CERTIFIED BY SCS Global Services