

# Wilshire Borghini

Color Body Glazed Porcelain Tile | Glazed Ceramic Tile



Produced In The USA  
2-3 week lead time

1 Color | 9 Formats | 4 Finishes

Featured: Wilshire Borghini | Venice Mosaic & 12" x 24"

## Details

### Color



Wilshire Borghini

**Installation Recommendation:**  
Choose a grout color that closely matches the tile.

## Formats

### Wall Tile Sizes Glazed Ceramic Tile



4" x 16"  
5/16" Thickness  
Gloss Finish/Matte Finish  
Pressed



4" x 16" Bucatini  
5/16" Thickness  
Matte Finish  
Pressed

### Close-up of 4" x 16" Bucatini



### Floor & Wall Tile Sizes Color Body Glazed Porcelain Tile



12" x 24"  
5/16" Thickness  
Natural Finish/Polished Finish  
Rectified



24" x 48"  
5/16" Thickness  
Polished Finish  
Rectified



24" x 48"  
3/8" Thickness  
Natural Finish  
Rectified

### Additional Formats Color Body Glazed Porcelain Tile



1.5" x 1.5" Mosaic  
5/16" Thickness  
Natural Finish/Polished Finish



12" x 14" Venice Mosaic  
5/16" Thickness  
Natural Finish/Polished Finish



0.76" x 0.76" Striata Mosaic  
5/16" Thickness  
Natural Finish/Polished Finish



3" x 12" Bullnose  
5/16" Thickness  
Natural Finish/Polished Finish

# Wilshire Borghini (continued)



<i>Symbols</i>	<i>Packing</i>	<i>Pcs/Box</i>	<i>SF/Box</i>	<i>Lbs/Box</i>
  	12" x 24"	7pcs	13.37 SF	52.09 Lbs
	24" x 48" Natural	2pcs	15.38 SF	76.02 Lbs
	24" x 48" Polished	2pcs	15.38 SF	64.87 Lbs
	4" x 16"	38pcs	16.73 SF	57.47 Lbs
	4" x 16" Bucatini	34pcs	14.97 SF	50.72 Lbs
	12" x 12" Mosaic	5pcs	5.53 SF	20.79 Lbs
	1.5" x 1.5" Mosaic	10pcs	9.56 SF	37.01 Lbs
	0.76" x 0.76" Striata Mosaic	10pcs	9.62 SF	37.01 Lbs
	3" x 12" Bullnose	15pcs	3.48 SF	16.01 Lbs

## TECHNICAL INFORMATION

	<i>Natural</i>	<i>Polished</i>	<i>Matte</i>	<i>Gloss</i>
Freeze Resistant	Resistant	Resistant	Resistant	Resistant
Shade Variation	V3	V3	V3	V3
Color Body	√	√	N/A	N/A
Water Absorption	≤0.5%	≤0.5%	≤7%	≤7%
Stain Resistant	Class A	Class E	Class C	Class E
DCOF AcuTest	≥0.42	<0.42	N/A	N/A
Chemical Resistant	Class A	Class E	Class C	Class E
Breaking Strength	≥ 275 lbf	≥ 275 lbf	≥ 250 lbf	≥ 250 lbf
Mohs Hardness	7	5	7	5

## AREAS OF USAGE

<i>Classification</i>	<i>Reference Category</i>	<i>Suitable</i>
Interior, Dry	ID	√
Interior, Wet	IW	√ NAT
Interior, Wet Plus	IW+	√ Mos NAT
Exterior, Wet	EW	
Oils/Greases	O/G	

## GROUT JOINT

*The recommended grout joint:*

**1/8"** Rectified

**3/16"** Pressed